

STD GRT-HORIZONTAL

- MODEL : US/STD GRT/H
- MAXIMUM COMPONENT OD : 400 MM
- MAXIMUM SHAFT TYPE COMPONENT GEAR OD : NA
- MIN/MAX SHAFT LENGTH : NA
- MIN/MAX CD : 65 / 280 MM
- FEATURES : ENGAGEMENT MECHANISM WITH LOCKING : LEAD SCREW FOR POSITIONING OF SLIDE
- ANALOG DIAL WITH 0.01MM LEAST COUNT
- HEAVY DUTY FABRICATED TABLE MOUNTING IF REQUIRED
- ANALOG DIAL WITH 0.001MM LEAST COUNT AVAILABLE ON REQUEST



STD GRT-VERTICAL

- MODEL : US/STD GRT/V
- MAXIMUM COMPONENT OD : 350MM
- MAXIMUM SHAFT TYPE COMPONENT GEAR OD : 380 MM
- MIN/MAX SHAFT LENGTH : 60 / 550 MM
- MIN/MAX CD : 65 / 280 MM
- FEATURES : ENGAGEMENT MECHANISM WITH LOCKING : SPRING LOADING ARRANGEMENT FOR BETWEEN CENTRE MOUNTING OF SHAFT TYPE GEARS : LEAD SCREW FOR POSITIONING OF SLIDE
- ANALOG DIAL WITH 0.01MM LEAST COUNT
- HEAVY DUTY FABRICATED TABLE MOUNTING IF REQUIRED
- ANALOG DIAL WITH 0.001MM LEAST COUNT AVAILABLE ON REQUEST